3149664571

Application No. 10/800,712 (Marsh) GAU 3632 Amnt. A coritd. Page 2 of 2

RECEIVED **CENTRAL FAX CENT程序** 

SEP 0 6 2007

## **CLAIMS**

Please amend the claims according to the status designations in the following list, which contains all claims submitted in the application, with the text of all active claims.

## 1 (CANCELED)

- 2. (NEW) An absorbent pad apparatus having a plurality of fabric layers of an outer layer size joined by a seam, having a bolstered center means, including a plurality of substantially fabric layers of a mid-portion size surrounding and attached to a third-layer wicking barrier, for capturing dripped condensate from a multi-serving vessel, comprised of:
- a. top-layer absorbent means of an outer-portion size, including at least one piece of cotton fabric, whereby condensate from a multi-serving vessel is drawn into the pad, preventing condensate from pooling on the surface of said pad; and
- b. second-layer desorption field means of an outer-portion size, including a piece of cotton batting, whereby the pad dries, thus eliminating the need for intervention during said pad's use; and
- c. third-layer wicking barrier means of a mid-portion size, including a piece of coated fabric, whereby absorbed moisture is forced to move in a radial direction: and
- d. bottom-layer thermal barrier means of an outer-portion size, including at least one piece of cotton batting, whereby secondary condensate is prevented from forming beneath the pad;
- e. wherein the pad apparatus of is of a size to exceed by one inch the bottom of the multi-serving vessel.